Docket No.: DHIN-0001-UT1 Application No. 10/623,186

Page 2 of 8

**IN THE CLAIMS** 

This listing of claims will replace all prior version, and listings, of claims in the application:

**Listing of Claims:** 

1-25. (Canceled).

26. (Currently amended) A method of illuminating a rotary blade comprising:

applying a layer of a primer and then a passively charged photoluminescent paint to a rotary blade; wherein the photoluminescent paint when activated has an extinction time of

greater than or equal to is luminous for at least about 5.5 hours.

27. (Previously presented) The method of claim 26, wherein said primer is reflective.

28. (Previously presented) The method of claim 27, wherein said reflective primer comprises

a urethane coating.

29. (Previously presented) The method of claim 28, wherein a first component of the

urethane coating comprises at least one polyester resin, at least one pigment, and at least one

solvent.

30. (Previously presented) The method of claim 28, wherein a second component of the

urethane coating comprises a resin and at least one solvent.

31. (Previously presented) The method of claim 26, further comprising:

sealing said passively charged photoluminescent paint with a substantially transparent

topcoat sealer.

32. (Currently amended) A method of illuminating a rotary blade comprising:

applying a layer of a white reflective primer coat and then a passively charged

photoluminescent paint to a rotary blade; and

Docket No.: DHIN-0001-UT1 Application No. 10/623,186

Page 3 of 8

wherein the photoluminescent paint when activated has an extinction time of greater than or equal to is luminous for at least about 5.5 hours.

33. (Previously presented) A method of illuminating a rotary blade comprising: applying a passively charged photoluminescent paint to a rotary blade; and sealing said passively charged photoluminescent paint with a topcoat sealer.

- 34. (Previously presented) The method of claim 33, wherein said topcoat sealer is substantially transparent.
- 35. (Previously presented) The method of claim 33, wherein said topcoat sealer comprises a urethane coating.
- 36. (Previously presented) The method of claim 35, wherein a first component of said urethane coating comprises at least one polyester resin, and at least one solvent.
- 37. (Previously presented) The method of claim 36, wherein a second component of said urethane coating comprises a resin and at least one solvent.
- 38. (Previously presented) A method of illuminating a rotary blade comprising: applying a passively charged photoluminescent paint to a rotary blade, wherein said passively charged photoluminescent paint comprises a urethane coating; and sealing said passively charged photoluminescent paint with a topcoat sealer.
- 39. (Previously presented) The method of claim 38, wherein said urethane coating further comprises at least one resin, at least one pigment, and at least one solvent.
- 40. (Previously presented) The method of claim 39, wherein said at least one resin comprises a polyester resin.

Docket No.: DHIN-0001-UT1 Application No. 10/623,186

Page 4 of 8

41. (Withdrawn) A photoluminescent paint system comprising a reflective primer coat, a passively charged photoluminescent coat disposed above at least a portion of said white reflective primer coat, and a substantially transparent topcoat sealer disposed above at least a portion of said passively charged photoluminescent coat.

42-49. (Canceled)